

Flooring that combines safety, durability and strength

WONDERFLOOR



Specially designed to provide extra grip for safe movements and high wear & tear resistance

The Wonderfloor SAFETY flooring is the ideal flooring designed for a long life with high wear and tear resistance, manufactured with "Multi-Layer Technology", this flooring is used in buses, metro coaches, trains and factories etc. for handling heavy traffic with extra grip. SAFETY flooring is available in "1.5 mm / 2.0 mm thickness" in various ranges of design patterns and colours such as embossed patterns, mosaic with quartz patterns, etc.

TECHNICAL SPECIFICATIONS		
CHARACTERISTICS	TEST METHOD	RESULT
DIMENSION • ROLLS	EN 426	2.00 MM - 2 MTR. X 15 MTR. = (30 SQ. MTR.)
THICKNESS- OVERALL	EN 428	2.0 MM / 1.5 MM
TOTAL WEIGHTEN	430	3.20 KG/SQ. MTR. FOR 2 MM
RESIDUAL INDENTATION AFTER STATIC LOAD	EN 433	_< 0.10 MM
DIMENSION STABILITY	EN 434	_<0.4%
FLEXIBILITY	■ EN 435	10 MM MANDREL, PASSES
ABRASION RESISTANCE	EN 660-2	WEAR GROUP P
SURFACE SPREAD OF FLAME	BS 476 PART 7	CLASS 1
FIRE PROPAGATION	BS 476 PART 6	(i) = 10.8 (ii) = 1.7 CLASS "0"
HORIZONTAL & VERTICAL BURNING TEST	IS 15061 - 2002 (ARA	NI) (PASS)
SOUND ABSORPTION	ISO 140-8	5 DB
COLOUR FASTNESS TO DAYLIGHT	ISO 105-B02	> BLUE WOOL STANDARD 7
SLIP RESISTANCE	DIN 51130	R 11
BEARING A CASTOR CHAIR	EN 425	SUITABLE
RESISTANCE TO CHEMICALS	EN 423	NO VISIBLE CHANGE
PREMORMANCE CLASSIFICATION	EN 685	33, 34













WONDERFLOOR- the world class vinyl flooring is a quality product from RMG Polyvinyl India Limited, an ISO 9001:2008 system approved company. We are the largest manufacturer & exporter for PVC floor coverings, films, sheeting and artificial leather. We manufacture a wide range of vinyl flooring in the state-of-the art plant & machinery equipped with latest technology and optimum quality control. We have a wide range of distribution network.

MAINTENANCE

Do's: • After laying of flooring, the surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution

- Prevent point load indentation by covering your furniture legs with rubber stopper caps.
- To remove stubborn stains, rub the affected area immediately with a soft coir brush or fine steel wool (No. 00 or 000) soaked in a warm soap solution.
- · Scuff marks on the floor can be removed with little application of diesel
- Use door coir or suitable mats to minimize accumulation of dust on Wonderfloor Vinyl Flooring.
- Use water to remove any chemical spill on flooring.
- Don'ts: Do not use any strong detergent, harsh cleaning agent and dry steel wool.
 - Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn-marks on the floor.
 - . Do not drag any heavy object or furniture on the flooring to avoid scratches on the floor





All products as per EN standards

RMG POLYVINYL INDIA LIMITED

Registered Office: 302, Illrd floor, Elite House, 36, Community Centre, Kailash Colony Extn., Zamrudpur, New Delhi-110048, Tel.: 0120-3118801/32118802, Fax: 011-66173679, E-mail: info@rmgpoly.com

Regional Offices : • Ahmedabad: 9377262959 • Bangalore: 9341263704 • Bhubaneswar: 9337423999 • Chandigarh: 93160 008724 • Chennai: 9380353335 • Cochin: 9387233952 • Guwahati: 9864016200 • Hyderabad: 9391051138 • Indore: 9329359269 • Kolkata: 9331023016 • Mumbai: 9323675979 • New Delhi: 011-41632022/24 • Pune: 9890096161 • Raipur: 9770683216