

WONDERFLOOR®
Vinyl Flooring

KRAYONS

*Flooring that combines durability,
style and performance*

The colourful flooring that adds freshness, joy and happiness to the interior


The Wonderfloor KRAYONS is the colorful range of flooring in lively natural shades to add freshness, cheerfulness and joy to the interiors. It's a designers' delight and the platform to integrate the creativeness by combining various shades and shapes.

The product is available in roll form and offer is recommended for moderate footfalls. Krayons is ideal for schools, playgroups, activity areas, children rooms etc.



TECHNICAL SPECIFICATIONS

CHARACTERISTICS	TEST METHOD	RESULT
Width (mtrs.)	IS : 3464:86	2.0 mtrs.
Total Thickness (mm)	IS : 3464:86	1.5 mm
Thickness of wear layer (mm)	EN 429	0.20 mm
Abrasion Resistance (cc)	ISO : 9352	0.35 cc (max.)
Dimension Stability (%)	IS : 3464:86	0.4% (max.)
Flexibility at Low temperature	IS : 3462:86	Shall not break, crack or show any other sign of failure
Residual Indentation (mm)	IS : 3464:86	0.10 (max.)
Moisture Movement (%)	IS : 3462:86	0.4% (max.)
Water extraction (%)	ASTMD 1239	0.35% (max.)
Colour Fastness to day light	IS 9766:81	Shall be rated not less than std. 4
Elongation at break (%)	IS : 3462:86	130% (min.)
Elastic Product (MJ/m ²)	IS : 3462:86	2.0 (min.)
Resistance to chemicals	Product are normally resistant to mild diluted acids & alkalies	No effect
Ply Adhesion (KN/M)	IS : 3464:86	1.05 (min.)
Ageing Properties	IS : 3464:86	No effect
Flammability	UIC-564-2 OR	Class B (min.)
Limiting oxygen index	IS : 13501	24 (min.)



For institutional / bulk enquiries, please e-mail : mkt@rmgpoly.com, or call : 9711200510
For export enquiries, please e-mail : info@rmgpoly.com Call: 98731 38885

WONDERFLOOR- the world class vinyl flooring is a quality product from RMG Polyvinyl India Limited, an ISO 9001:2008 system approved company. We are the largest manufacturer & exporter for PVC floor coverings, films, sheeting and artificial leather. We manufacture a wide range of vinyl flooring in the state-of-the art plant & machinery equipped with latest technology and optimum quality control. We have a wide range of distribution network.

MAINTENANCE

- Do's :
- After laying of flooring, the surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution
 - Prevent point load indentation by covering your furniture legs with rubber stopper caps.
 - To remove stubborn stains, rub the affected area immediately with a soft coir brush or fine steel wool (No. 00 or 000) soaked in a warm soap solution.
 - Scuff marks on the floor can be removed with little application of diesel.
 - Use door coir or suitable mats to minimize accumulation of dust on Wonderfloor Vinyl Flooring.
 - Use water to remove any chemical spill on flooring.
- Don'ts :
- Do not use any strong detergent, harsh cleaning agent and dry steel wool.
 - Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn-marks on the floor.
 - Do not drag any heavy object or furniture on the flooring to avoid scratches on the floor.



All products as per EN standards

RMG POLYVINYL INDIA LIMITED

Registered Office : 302, IIIrd floor, Elite House, 36, Community Centre, Kailash Colony Extn., Zamrudpur, New Delhi-110048,
Tel.: 0120-3118801/32118802, Fax: 011-66173679, E-mail: info@rmgpoly.com

Regional Offices : • Ahmedabad: 9377262959 • Bangalore: 9341263704 • Bhubaneswar: 9337423999 • Chandigarh: 93160 008724 • Chennai: 9380353335
• Cochin: 9387233952 • Guwahati: 9864016200 • Hyderabad: 9391051138 • Indore: 9329359269 • Kolkata: 9331023016
• Mumbai: 9323675979 • New Delhi: 011-41632022/24 • Pune: 9890096161 • Raipur: 9770683216

www.rmgpoly.com, www.wonderfloor.com

WONDERFLOOR is the registered Trade Mark of RMG Polyvinyl India Limited